

*Note: In the process of enhancing our systems, we are transitioning data to a new PiQ data view. This data is being verified with the "Historical" view for accuracy. Once the data is confirmed, the "Historical" view will be discontinued. During this transition, you may encounter duplicate entries or missing/outdated data. For queries during this interim period, please visit our [Historical View FAQs](#) or contact our [Customer Service](#).*

## Fire-exit Hardware

### COMPANY

#### Masdar Hardware

P.O. Box 42300

Riyadh, 11541 Saudi Arabia

R39595

#### Investigated to ANSI/BHMA A156.3 (2008) Grade 1

**Rim types** Model(s) E18-F5000, E18-F5000-1

#### Investigated to ANSI/BHMA A156.3 (2014) Grade 1, ANSI/UL 10C

**Concealed vertical rod devices with auxiliary fire latch for LBR devices** Model(s) E18-8550F

**Concealed vertical rod devices with auxiliary fire latch for LBR devices, for use on doors not exceeding 10 ft. in height** Model(s) E18-8650F

**Single point mortise lock devices** Model(s) E18-8620F, E18-8820F

**Single point rim type latches** Model(s) E18-8510F, E18-8610F, E18-8810F

**Surface mounted vertical rod devices with auxiliary fire latch for LBR devices** Model(s) E18-8530F

**Surface mounted vertical rod devices with auxiliary fire latch for LBR devices, for use on doors not exceeding 10 ft. in height** Model(s) E18-8630F

#### Investigated to ANSI/BHMA A156.3 (2014) Grade 1, ANSI/UL 10C, ANSI/UL 305

**Concealed vertical rod devices with auxiliary fire latch for LBR devices** Model(s) E18-8750F

**Concealed vertical rod devices with auxiliary fire latch for LBR devices, for use on doors not exceeding 10 ft. in height** Model(s) E18-8850F

**Single point rim type latches** Model(s) E18-8710F

**Surface mounted vertical rod devices with auxiliary fire latch for LBR devices** Model(s) E18-8730F

**Surface mounted vertical rod devices with auxiliary fire latch for LBR devices, for use on doors not exceeding 10 ft. in height** Model(s) E18-8830F

#### Investigated to ANSI/UL 10C

**Single point rim type latches, may be provided with the Series 6000 mullions** Model(s) E18-2085

**Surface mounted vertical rod type latches, for use on egress and pairs of swinging fire doors rated up to 1-1/2 hrs.** Model(s) E18-2086

**Surface-mounted vertical rod types** Model(s) E18-F5600, E18-F5600-1

Trademark and/or Tradename: "LOGIC", "¿LOGIC Hardware¿", 

---

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."